

# SUPREME TUBE TESTER MODEL 35 OPERATING DATA TUBE LIST

NON-OCTAL TUBES				OCTAL TUBES				FUTURE OCTAL TUBES			
Type	Fil.V. Slctr.	Qty. Slctr.	But-tons	Type	Fil.V. Slctr.	Qty. Slctr.	But-tons	Type	Fil.V. Slctr.	Qty. Slctr.	But-tons
10X	7.5	73.0	3	482A/71A	5.0	57.0	3	6H7	6.3	46.0	2
1A4	7.5	71.0	3	482B/182B	5.0	60.0	3	6J7	6.3	46.0	2
1A6	5.0	53.0	3	483/183	5.0	56.5	3	6K6	6.3	56.0	2
1B4	14.0	51.5	5	484	3.3	42.5	5	6K7	6.3	47.5	2
1B5/25S/25	14.0	71.0	5	484A	2.5	47.5	5	6L6	6.3	32.5	2
1C6	14.0	55.0	5	485	3.3	48.0	5	6L7	6.3	35.0	2
1F4	14.0	44.0	5	486/686	3.3	74.5	3	6N6	6.3	62.0	2
2A3/2A3H	2.0	46.0	3	585/586/50	7.5	69.0	3	6P7	6.3	51.0	1
2A6/2A6S	2.5	31.5	3	686/486	3.3	74.5	3	6Q7	6.3	40.0	2
2A7/2A7S	2.5	45.0	5	950	2.0	63.0	3	6R7	6.3	41.5	2
2B6	2.5	43.0	5	951	2.0	61.5	3	6X5	6.3	24.0	2
2B7/2B7S	2.5	59.5	5	985/84/6Z4	6.3	23.5	5	6Z6	6.3	23.5	2
2Y4	2.5	55.0	5	986/83	5.0	53.5	3	25A6	25.0	34.0	2
2Z2/G84	2.5	30.5	3	AD/6Z3/1V	6.3	29.0	1	25Z5	25.0	6.5	2
5Z3	2.5	75.0	3	AF/82	2.5	55.5	3	25Z6	25.0	13.0	2
6A3	5.0	42.0	3	AG/83	5.0	53.5	3	27	2.5	57.5	2
6A4/LA	6.3	40.5	3	DE1/27/27S	2.5	57.0	5	35/51	2.5	59.0	2
6A6	6.3	57.0	3	GA	5.0	53.0	3	41	6.3	53.5	2
6A7/6A7S	6.3	27.0	7	G84/2Z2	2.5	75.0	3	43	6.3	44.5	2
6B5	6.3	44.5	5	KR-1	6.3	29.0	1	51/35	2.5	32.0	2
6B6	6.3	44.5	5	KR-5	6.3	57.0	3	55	2.5	53.5	2
6B7/6B7S	6.3	62.5	3	KR-20	3.3	40.5	5	56	2.5	58.0	2
6C6	6.3	57.5	5	LA/6A4	6.3	57.0	3	57	2.5	50.0	2
6C7	6.3	46.5	5	P861/84/6Z4	6.3	23.5	5	58	2.5	49.0	2
6D6	6.3	47.0	5	PA	6.3	46.5	5	59	6.3	40.0	2
6E6	6.3	42.0	7	PZ/47	2.5	52.0	3	75	6.3	47.0	2
6E7	6.3	33.5	5	PZH	2.5	51.5	5	77	6.3	53.0	2
6F7/6F7S	6.3	42.0	5	R-20	2.5	57.5	5	80	6.3	58.0	2
6G7S/89RS	6.3	33.5	7	R-30	2.5	61.5	5	81	6.3	54.5	2
6H7S	6.3	45.0	5	R-32	2.5	63.5	3	82	6.3	51.5	2
6Y5/6Y5S	6.3	49.0	5	R-100	5.0	73.5	3	85	6.3	51.5	2
6Z3/1V	6.3	22.5	1	R-200	5.0	70.0	3	86	6.3	46.5	2
6Z4/84	6.3	46.0	6	RE1/80	5.0	52.5	3	88	6.3	45.0	2
6Z5	6.3	21.5	6	RE2/81	5.0	85.0	3	89	6.3	40.0	2
12A5	12.6*	29.0	1	RK-24	2.0	60.0	3	90	6.3	47.0	2
12A7	12.6	23.5	5	SO2/50	7.5	69.0	3	91	6.3	47.0	2
12Z3/14Z3	12.6	22.5	6	WUND-A	2.5	53.5	5	92	6.3	47.0	2
12Z5	12.6†	22.5	6	WUND-AA	6.3	54.5	5	93	6.3	47.0	2
14Z3/12Z3	12.6	54.5	6					94	6.3	47.0	2
25Y5	25.0	21.0	1					95	6.3	47.0	2
25Z5	25.0	18.0	1					96	6.3	47.0	2
00A	5.0	15.0	1					97	6.3	47.0	2
01A	5.0	18.0	1					98	6.3	47.0	2
01AA/01B	5.0	28.5	1					99	6.3	47.0	2
1V/6Z3	6.3	9.0	3					100	6.3	47.0	2
2S/4S	2.5	60.5	3					101	6.3	47.0	2
4S/2S	2.5	74.0	3					102	6.3	47.0	2
	2.5	73.0	3					103	6.3	47.0	2
	2.5	44.5	1					104	6.3	47.0	2
	2.5	29.0	1					105	6.3	47.0	2
	2.5	83.0	5					106	6.3	47.0	2
	2.5	88.0	5					107	6.3	47.0	2
	2.5	29.0	1					108	6.3	47.0	2
	2.5	83.0	5					109	6.3	47.0	2
	2.5	88.0	5					110	6.3	47.0	2
	2.5	29.0	1					111	6.3	47.0	2
	2.5	83.0	5					112	6.3	47.0	2
	2.5	88.0	5					113	6.3	47.0	2
	2.5	29.0	1					114	6.3	47.0	2
	2.5	83.0	5					115	6.3	47.0	2
	2.5	88.0	5					116	6.3	47.0	2
	2.5	29.0	1					117	6.3	47.0	2
	2.5	83.0	5					118	6.3	47.0	2
	2.5	88.0	5					119	6.3	47.0	2
	2.5	29.0	1					120	6.3	47.0	2
	2.5	83.0	5					121	6.3	47.0	2
	2.5	88.0	5					122	6.3	47.0	2
	2.5	29.0	1					123	6.3	47.0	2
	2.5	83.0	5					124	6.3	47.0	2
	2.5	88.0	5					125	6.3	47.0	2
	2.5	29.0	1					126	6.3	47.0	2
	2.5	83.0	5					127	6.3	47.0	2
	2.5	88.0	5					128	6.3	47.0	2
	2.5	29.0	1					129	6.3	47.0	2
	2.5	83.0	5					130	6.3	47.0	2
	2.5	88.0	5					131	6.3	47.0	2
	2.5	29.0	1					132	6.3	47.0	2
	2.5	83.0	5					133	6.3	47.0	2
	2.5	88.0	5					134	6.3	47.0	2
	2.5	29.0	1					135	6.3	47.0	2
	2.5	83.0	5					136	6.3	47.0	2
	2.5	88.0	5					137	6.3	47.0	2
	2.5	29.0	1					138	6.3	47.0	2
	2.5	83.0	5					139	6.3	47.0	2
	2.5	88.0	5					140	6.3	47.0	2

**OCTAL TUBES**  
 NOTE:—Octal types differing in designation from the following by an additional final letter "G", "R", "M", "MG" are interchangeable in general, regardless of the letter, as it simply denotes the type of shell employed by individual manufacturers, and take the same tester settings.

**FUTURE NON-OCTAL TUBES**

**FUTURE OCTAL TUBES**

\* For 6Z5 tube tests, throw the "6Z5" tumbler switch from the "NORMAL" to the "6Z5" position during the tests.  
 † For 12A5 tube tests, throw the "12A5" tumbler switch from the "NORMAL" to the "12A5" position during the tests.  
 ‡ For 12Z5 tube tests, throw the "12Z5" tumbler switch from the "NORMAL" to the "12Z5" position during the tests.

(A) Use Orange Adapter No. 7173. (B) Use Violet Adapter No. 7174. (C) Use Black Adapter No. 7136. (E) Use Adapter No. 7530.

**Supreme Instruments Corporation, Greenwood, Mississippi, U. S. A.**

**GROUP "A"**  
(Most Popular Tubes)

01A	-	5.0	-	73.0	-	3
24A	-	2.5	-	50.0	-	5
26	-	1.5	-	67.5	-	3
27	-	2.5	-	52.0	-	5
35	-	2.5	-	48.0	-	5
45	-	2.5	-	49.5	-	3
47	-	2.5	-	47.0	-	3
71A	-	5.0	-	59.0	-	3
80	-	5.0	-	51.0	-	3

**GROUP "B"**  
(Complete Tube List)

1A6	-	2.0	-	76.5	-	3
1C6	-	2.0	-	72.0	-	3
2A3	-	2.5	-	31.0	-	3
2A3H	-	2.5	-	32.0	-	3
2A5	-	2.5	-	47.0	-	5
2A6	-	2.5	-	37.0	-	5
2A7	-	2.5	-	42.0	-	5
2B6	-	2.5	-	40.0	-	5
2B7	-	2.5	-	59.0	-	5
2Y4	-	2.5	-	30.5	-	5
5Z3	-	5.0	-	47.5	-	3
6A3	-	6.3	-	55.0	-	1
6A4	-	6.3	-	56.0	-	3
6A7	-	6.3	-	41.5	-	5
6B7	-	6.3	-	53.0	-	5
6C6	-	6.3	-	43.0	-	5
6C7	-	6.3	-	39.5	-	5
6D6	-	6.3	-	44.0	-	5

6D7	-	6.3	-	38.0	-	5
6E7	-	6.3	-	42.5	-	5
6F7	-	6.3	-	46.5	-	5
6G7S	-	6.3	-	18.5	-	1&6
6Y5	-	6.3	-	54.0	-	6
6Y5V	-	6.3	-	27.0	-	6
6Z3	-	6.3	-	29.5	-	1
6Z4	-	6.3	-	26.0	-	5
*6Z5	-	12.0	-	28.0	-	6
† 12A5	-	12.0	-	51.0	-	6
12A7	-	12.0	-	25.0	-	5&7
12Z3	-	12.0	-	21.0	-	1
† 12Z5	-	12.0	-	13.0	-	1&6
14Z3	-	14.0	-	21.0	-	1
25Z5	-	25.0	-	16.0	-	1&6
00A	-	5.0	-	63.0	-	3
01A	-	5.0	-	73.0	-	3
KR1	-	6.3	-	29.5	-	1
1v	-	6.3	-	29.5	-	1
1	-	6.3	-	51.0	-	1
G2S	-	2.5	-	70.0	-	5
G4S	-	2.5	-	85.0	-	5
10	-	7.5	-	72.5	-	3
10X	-	7.5	-	72.0	-	3
12A	-	5.0	-	50.0	-	3
14	-	14.0	-	51.0	-	5
15	-	2.0	-	74.0	-	5
17	-	14.0	-	53.0	-	5
18	-	14.0	-	40.0	-	5
19	-	2.0	-	48.5	-	3
KR20	-	2.5	-	45.0	-	5
20	-	3.3	-	98.0	-	3

22	-	3.3	-	80.0	-	3
KR22	-	6.3	-	39.0	-	5
24A	-	2.5	-	50.0	-	5
25S	-	2.0	-	79.0	-	3
26	-	1.5	-	67.5	-	3
27HM	-	2.5	-	39.5	-	5
27	-	2.5	-	52.0	-	5
29	-	2.5	-	43.0	-	5
30	-	2.0	-	75.0	-	3
30X	-	2.0	-	75.0	-	3
31	-	2.0	-	71.5	-	3
32	-	2.0	-	74.0	-	3
33	-	2.0	-	58.0	-	3
34	-	2.0	-	83.0	-	3
35	-	2.5	-	48.0	-	5
36	-	6.3	-	41.5	-	5
37	-	6.3	-	53.0	-	5
38	-	6.3	-	49.5	-	5
39	-	6.3	-	49.0	-	5
40	-	5.0	-	73.0	-	3
41	-	6.3	-	42.0	-	5
42A	-	2.5	-	39.5	-	5
42	-	6.3	-	43.5	-	5
43C	-	25.0	-	33.5	-	5
43	-	25.0	-	31.5	-	5
44	-	6.3	-	49.0	-	5
45	-	2.5	-	49.5	-	3
46	-	2.5	-	48.0	-	3
47	-	2.5	-	47.0	-	3
48	-	30.0	-	33.5	-	5
49	-	2.0	-	63.5	-	3
50	-	7.5	-	65.0	-	3

51	-	2.5	-	48.0	-	5
52	-	6.3	-	48.5	-	3
53	-	2.5	-	30.5	-	7
55	-	2.5	-	45.5	-	5
56	-	2.5	-	39.5	-	5
57	-	2.5	-	36.0	-	5
57A	-	6.3	-	36.5	-	5
58	-	2.5	-	40.5	-	5
58A	-	6.3	-	41.0	-	5
59	-	2.5	-	39.5	-	5
59B	-	2.5	-	47.5	-	3
64A	-	6.3	-	43.5	-	5
64	-	6.3	-	55.5	-	5
65A	-	6.3	-	47.5	-	5
65	-	6.3	-	45.0	-	5
67A	-	6.3	-	45.0	-	5
67	-	6.3	-	49.5	-	5
68	-	6.3	-	43.5	-	5
68A	-	6.3	-	45.5	-	5
69	-	6.3	-	45.5	-	5
70	-	6.3	-	82.0	-	5
71A	-	5.0	-	59.0	-	3
75	-	6.3	-	35.5	-	5
76	-	6.3	-	36.0	-	5
77	-	6.3	-	40.0	-	5
78	-	6.3	-	45.0	-	5
79	-	6.3	-	27.0	-	6
80M	-	5.0	-	50.0	-	3
80	-	5.0	-	51.0	-	3
81M	-	7.5	-	91.0	-	3
81	-	7.5	-	91.0	-	3
82	-	2.5	-	50.0	-	2

83v	-	5.0	-	26.0	-	3
83	-	5.0	-	50.0	-	3
G84	-	2.5	-	90.5	-	3
84	-	6.3	-	26.0	-	5
85	-	6.3	-	41.0	-	5
87S	-	6.3	-	41.5	-	5
88	-	5.0	-	50.0	-	3
88S	-	6.3	-	43.5	-	5
89	-	6.3	-	43.5	-	5
89RS	-	6.3	-	18.5	-	1&6
90	-	2.5	-	45.0	-	5
92	-	6.3	-	39.0	-	5
95	-	2.5	-	46.0	-	5
98	-	6.3	-	26.0	-	5
99	-	3.3	-	100.0	-	3
181S	-	3.3	-	64.5	-	3
182	-	5.0	-	58.5	-	3
182A	-	5.0	-	58.5	-	3
182B	-	5.0	-	58.5	-	3
183	-	5.0	-	56.0	-	3
205D	-	5.0	-	72.0	-	3
257	-	5.0	-	68.0	-	3
401	-	3.3	-	57.5	-	3
403	-	3.3	-	56.0	-	3
410	-	7.5	-	72.5	-	3
420	-	3.3	-	98.0	-	3
422	-	3.3	-	80.0	-	3
431	-	2.0	-	71.5	-	3
445	-	2.5	-	49.5	-	3
450	-	7.5	-	65.0	-	3
481	-	7.5	-	91.0	-	3
482	-	5.0	-	58.5	-	3



**[www.StevenJohnson.com](http://www.StevenJohnson.com)**

**Antique Technolgy, Tube Radios and Test Equipment  
Vintage Schematics, and Publications**

**Steve's Antique Technology**