

SUPREME 385 AUTOMATIC TUBE LIST

(Specify "R" Series Tube Chart When Re-ordering)

NON-OCTAL TUBES																								
Type	Fil.V. Slctr.	Fil.Ret. Slctr.	Qty. Slctr.	But-tons	Type	Fil.V. Slctr.	Fil.Ret. Slctr.	Qty. Slctr.	But-tons	Type	Fil.V. Slctr.	Fil.Ret. Slctr.	Qty. Slctr.	But-tons	Type	Fil.V. Slctr.	Fil.Ret. Slctr.	Qty. Slctr.	But-tons					
1A4	2.0	7	75.0	F	01AA/01B	5.0	7	70.0	F	48	30.0	7	47.0	5	89RS/6G7S	6.3	7	46.0	3&5	RE1/80	5.0	7	68.0	F
1A6	2.0	7	74.5	F	1	6.3	7	67.0	3	48 (Spec.)	14.0	7	68.5	F	95/2A5	2.5	7	65.0	5	RE2/81	7.5	7	76.5	F
1B4	2.0	7	76.0	F	1V/6Z3	6.3	7	48.0	3	49	2.0	7	71.5	F	96/1V	6.3	7	48.0	3	RK-24	2.0	7	71.0	F
1B5/25S/25	2.0	7	73.0	F	2S/4S	2.5	7	74.5	4	50	7.5	7	71.5	F	98/84	6.3	7	43.5	4	SO2/50	7.5	7	71.5	F
1C6	2.0	7	70.5	F	4S/2S	2.5	7	74.5	4	51/35	2.5	7	68.5	4	99-O	3.3	7	81.0	F	WUND-A	2.5	7	69.0	5
1F4	2.0	7	70.0	F	10	7.5	7	72.0	F	51S/35S	2.5	7	68.5	4	99-T	3.3	7	80.5	F	WUND-AA	6.3	7	69.0	5
2A3/2A3H	2.5	7	46.5	F	10X	7.5	7	71.5	F	52	6.3	7	67.0	F	Future Non-Octal Tubes									
2A5	2.5	7	65.0	5	12A	5.0	7	68.0	F	53	2.5	7	48.5	4	Type	Fil.V. Selector	Fil.Ret. Selector	Quality Selector	But-tons					
2A6/2A6S	2.5	7	68.0	5	14	14.0	7	68.5	4	55/55S	2.5	7	68.0	5	-----	-----	-----	-----	-----					
2A7/2A7S	2.5	7	65.5	6	15	2.0	7	76.0	4	56/56S	2.5	7	68.0	4	-----	-----	-----	-----	-----					
2B6	2.5	7	69.5	5&6	17	14.0	7	69.0	4	56AS	6.3	7	67.0	4	-----	-----	-----	-----	-----					
2B7/2B7S	2.5	7	69.0	6	18	14.0	7	65.0	5	57/57S	2.5	7	63.0	5	-----	-----	-----	-----	-----					
2Y4	2.5	7	51.5	4	19	2.0	7	67.5	F	57AS	6.3	7	63.0	5	-----	-----	-----	-----	-----					
2Z2/G84	2.5	7	73.5	F	20	3.3	7	79.5	F	58/58S	2.5	7	64.0	5	-----	-----	-----	-----	-----					
5Z3	5.0	7	55.0	F	22-O	3.3	7	73.5	F	58AS	6.3	7	65.5	5	-----	-----	-----	-----	-----					
6A3	6.3	7	51.0	F	22-T	3.3	7	89.0	F	59	2.5	7	64.5	6	-----	-----	-----	-----	-----					
6A4/LA	6.3	7	68.0	F	22(Spec.)	14.0	7	69.5	F	59B	2.5	7	67.5	F	-----	-----	-----	-----	-----					
6A6	6.3	7	46.5	4	24A/24S	2.5	7	68.0	4	64	6.3	7	70.0	4	-----	-----	-----	-----	-----					
6A7/6A7S	6.3	7	66.5	6	25/25S/1B5	2.0	7	73.0	F	64A	6.3	7	65.5	4	-----	-----	-----	-----	-----					
6B5	6.3	7	70.0	F&5	26	1.5	7	71.0	F	65	6.3	7	67.5	4	-----	-----	-----	-----	-----					
6B6	6.3	7	68.0	5&6	26 (Spec.)	14.0	7	68.0	F	65A	6.3	7	68.0	4	-----	-----	-----	-----	-----					
6B7/6B7S	6.3	7	69.5	6	27/27S	2.5	7	69.0	4	67	6.3	7	69.0	4	-----	-----	-----	-----	-----					
6C6	6.3	7	65.5	5	27HM/56	2.5	7	68.0	4	67A	6.3	7	67.0	4	-----	-----	-----	-----	-----					
6C7	6.3	7	64.5	6	29	2.5	7	69.0	5	68	6.3	7	66.5	4	-----	-----	-----	-----	-----					
6D6	6.3	7	66.5	5	30	2.0	7	73.0	F	68A	6.3	7	69.0	4	-----	-----	-----	-----	-----					
6D7	6.3	7	64.0	6	30 (Spec.)	14.0	7	70.0	F	69	6.3	7	68.5	5	-----	-----	-----	-----	-----					
6E6	6.3	7	53.0	4	30-X	2.0	7	73.5	F	70	6.3	7	75.5	5	-----	-----	-----	-----	-----					
6E7	6.3	7	66.5	6	31	2.0	7	72.0	F	71A/482A	5.0	7	68.5	F	-----	-----	-----	-----	-----					
6F7/6F7S	6.3	7	68.0	6	32	2.0	7	74.0	F	75/75S	6.3	7	61.0	5	-----	-----	-----	-----	-----					
6G7S/89RS	6.3	7	46.0	3&5	32 (Spec.)	14.0	7	67.0	F	76	6.3	7	67.0	4	-----	-----	-----	-----	-----					
6H7S	6.3	7	68.0	6	33	2.0	7	69.5	F	77	6.3	7	66.0	5	-----	-----	-----	-----	-----					
6Y5/6Y5S	6.3	7	44.0	4	34	2.0	7	74.0	F	78	6.3	7	68.0	5	-----	-----	-----	-----	-----					
6Y5V	6.3	7	48.0	4	35/51	2.5	7	68.5	4	79	6.3	7	47.5	4	-----	-----	-----	-----	-----					
6Z3/1V	6.3	7	48.0	3	35S/51S	2.5	7	68.5	4	80	5.0	7	68.0	F	-----	-----	-----	-----	-----					
6Z4/84	6.3	7	43.5	4	36/36A	6.3	7	63.5	4	80M/83	5.0	7	21.0	F	-----	-----	-----	-----	-----					
6Z5	12.6(a)	7	44.5	4	37/37A	6.3	7	68.0	4	81/81M	7.5	7	76.5	F	-----	-----	-----	-----	-----					
12A5	12.6(b)	7	68.0	5	38/38A	6.3	7	69.0	4	82/AF	2.5	7	22.5	F	-----	-----	-----	-----	-----					
12A7	12.6	7	43.0	4&6	39/44/39A	6.3	7	68.0	4	83/AG/986	5.0	7	21.0	F	-----	-----	-----	-----	-----					
12Z3/14Z3	12.6	7	43.0	3	40	5.0	7	72.5	F	83V	5.0	7	41.0	F	-----	-----	-----	-----	-----					
12Z5	12.6(c)	7	41.0	3&5	40 (Spec.)	14.0	7	59.0	F	84/6Z4	6.3	7	43.5	4	-----	-----	-----	-----	-----					
14Z3/12Z3	12.6	7	43.0	3	41	6.3	7	63.0	5	85/85S	6.3	7	65.0	5	-----	-----	-----	-----	-----					
25Y5	25.0	7	48.5	3&4	42	6.3	7	66.0	5	85AS	6.3	7	64.0	5	-----	-----	-----	-----	-----					
25Z5	25.0	7	37.0	3&4	43	25.0	7	52.0	5	86	6.3	7	68.0	4	-----	-----	-----	-----	-----					
00A	5.0	7	75.5	F	44/39/39A	6.3	7	68.0	4	87S	6.3	7	61.0	5	-----	-----	-----	-----	-----					
01A	5.0	7	74.5	F	45	2.5	7	68.0	F	88/83	5.0	7	21.0	F	-----	-----	-----	-----	-----					
					46	2.5	7	68.0	F	88S	6.3	7	65.0	5	-----	-----	-----	-----	-----					
					47/PZ	2.5	7	68.0	F	89	6.3	7	67.5	5	-----	-----	-----	-----	-----					

- (a) Throw the "6Z5" tumbler switch from the "NORMAL" to the "6Z5" position during the test.
- (b) Throw the "12A5" tumbler switch from the "NORMAL" to the "12A5" position during the test.
- (c) Throw the "12Z5" tumbler switch from the "NORMAL" to the "12Z5" position during the test.
- (d) Throw the "12A5" and "12Z5" tumbler switches from the "NORMAL" to the "12A5" and "12Z5" positions during the test.
- (e) Use No. 7530 Adapter.

SUPREME INSTRUMENTS CORPORATION, Greenwood, Mississippi, U. S. A.



www.StevenJohnson.com

**Antique Technolgy, Tube Radios and Test Equipment
Vintage Schematics, and Publications**

Steve's Antique Technology